



PRINT THIS PAGE

1500/3000 rpm 50 Hz – cos ϕ 0,8 230V – 400/230V **1800/3600 rpm** 60 Hz – cos ϕ 0,8 **voltage on request**

AGRIGEN SERIES



STANDARD EQUIPMENT for AP..T-IP and AP..TL-IP

- Protection cover IP44 (splash-proof), three-point coupling, PTO protection cover
- Gear oil type SAE90EP (first filling incl.)
- Ground spike with 5 m cable
- Instruments: 1 x voltmeter, 1 x frequency meter, 1 x ammeter
- Socket kit: 1 x Schuko and 1 x CEE 6h 5-p sockets with RCCB and circuit breaker

PTO SHAFT GENERATORS AP..T-IP



MODEL	kVA (kW)	Sockets	Coupling Category	PTO Connection	Gear Ratio	PTO r.p.m. (50 Hz)	Voltage regulation	Min. Power	Tractor Power (HP)~	Dimensions				Category 2 Adaptor	4 Transport Wheels	3PH -sensing voltage regulator	Manualloads with V-HZ-Air
										L	W	H	kg				
2-POLE 3000/3600 rpm																	
AP15T-IP	16 (12,8)	1x32A 5-p CEE - 1xSchuko 16A/230V	1	1",3/8 Z6	1:7	430	Compound	18 (25)	> 45	100	67	110	195	o	o	–	o
AP20T-IP	22 (17,6)	1x32A 5-p CEE - 1xSchuko 16A/230V	1	1",3/8 Z6	1:7	430	Compound	23 (32)	> 60	100	67	110	270	o	o	–	o
AP30T-IP	27 (21,6)	1x63A 5-p CEE - 1xSchuko 16A/230V	1	1",3/8 Z6	1:7	430	Compound	32 (44)	> 80	100	67	110	300	o	o	–	o
2-POLE 1500/1800 rpm																	
AP20TL-IP	20 (16)	1x32A 5-p CEE - 1xSchuko 16A/230V	1	1",3/8 Z6	1:3,5	430	Electronic	21 (29)	> 60	100	67	110	270	o	o	•	o

AP30TL-IP	30 (24)	1x63A 5-p CEE - 1xSchuko 16A/230V	1	1",3/8 Z6	1:3,5	430	Electronic	32 (44)	> 80	100	67	110	300	o	o	•	o
AP40TL-IP	42 (33,6)	1x63A 5-p CEE - 1xSchuko 16A/230V	2	1",3/8 Z6	1:3,5	430	Electronic	45 (61)	> 100	100	67	110	350	•	o	•	o
AP50TL-IP	50 (40)	1x125A 5-p CEE - 1xSchuko 16A/230V	2	1",3/8 Z6	1:3,5	430	Electronic	56 (75)	> 125	130	85	110	500	-	o	•	o
AP60TL-IP	60 (48)	1x125A 5-p CEE - 1xSchuko 16A/230V	2	1",3/8 Z6	1:3,5	430	Electronic	67 (90)	> 140	130	85	110	520	-	o	•	o
AP80TL-IP	80 (64)	"1x125A 5-p CEE - 1xSchuko 16A/230V"	2	1",3/8 Z6	1:3,5	430	Electronic	90 (125)	> 160	130	85	110	610	-	o	•	o

Edit Table

LEGEND: • = standard o = on request - = not available

PTO SHAFT GENERATORS AP..TL-IP

MODEL	kVA (kW)	Sockets	Coupling Category	PTO Connection	Gear Ratio	PTO r.p.m. (50 Hz)	Voltage regulation	Min. Power	Tractor Power (HP)**						ACCESSORIES FIELD OPERATION		
										L	W	H	kg		Category 2 Adaptor	4 Transport Wheels	3PH -sensing voltage regulator
cosPhi 0,8 400V 50 Hz										at PTO shaft kW (HP)							
4-POLE 1500/1800 rpm																	
AP20TL-IPE	20 (16)	1x32A 5-p 6H 1xSchuko 16A/230V - 1x32A 5-p 1H	1	1",3/8 Z6	1:3,5	430	Electronic	21 (29)	> 60	100	67	110	275	o	o	•	c
AP30TL-IPE	30 (24)	1x32A + 1x16A 5-p 6H 1xSchuko 16A/230V - 1x63A 5-p 1H	1	1",3/8 Z6	1:3,5	430	Electronic	32 (44)	> 80	100	67	110	300	o	o	•	c
AP40TL-IPE	42 (33,6)	1x32A + 1x16A 5-p 6H 1xSchuko 16A/230V - 1x63A 5-p 1H	2	1",3/8 Z6	1:3,5	430	Electronic	45 (61)	> 100	100	67	110	355	•	o	•	c
AP50TL-IPE	50 (40)	1x63A + 1x16A 5-p 6H 1xSchuko 16A/230V - 1x125A 5-p 1H	2	1",3/8 Z6	1:3,5	430	Electronic	56 (75)	> 125	130	85	110	500	-	o	•	c
AP60TL-IPE	60 (48)	1x63A + 1x16A 5-p 6H 1xSchuko 16A/230V - 1x125A 5-p 1H	2	1",3/8 Z6	1:3,5	430	Electronic	67 (90)	> 140	130	85	110	525	-	o	•	c
AP80TL-IPE	80 (64)	1x63A + 1x16A 5-p 6H 1xSchuko 16A/230V - 1x125A 5-p 1H	2	1",3/8 Z6	1:3,5	430	Electronic	90 (125)	> 160	130	85	110	615	-	o	•	c
AP100TL-IPE	100 (80)	1x63A + 1x32A 5-p 6H 1xSchuko 16A/230V - PowerLock 5x400A	2	1",3/4 Z20	1:2	750	Electronic	115 (160)	> 200	130	85	110	650	-	o	•	c
AP130TL-IPE	130 (104)	1x63A + 1x32A 5-p 6H 1xSchuko 16A/230V - PowerLock 5x400A	3	1",3/4 Z20	1:2	750	Electronic	150 (210)	> 250	130	85	110	720	-	o	•	c

Edit Table

LEGEND: • = standard o = on request - = not available



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: [+39 0523 512401](tel:+390523512401)

Fax: [+39 0523 504453](tel:+390523504453)

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: [+39 0523 512440](tel:+390523512440) Fax: [+39 0523 504453](tel:+390523504453)

E mail: export@tecnogen.com