



PRINT THIS PAGE

3000 rpm 50 Hz – cos φ 0,8 230V – 400/230V 3600 rpm 60 Hz – cos φ 0,8 voltage on request

COMPACT SERIES

GASOLINE Air Cooled

POWERED by HONDA



STANDARD EQUIPMENT

- Protection frame
- Low oil level protection
- Exhaust gas silencer
- Air filter
- Fuel tank
- Output sockets with thermal protection or circuit breaker
- 12V Battery on electric started models

COMPACT SERIES

MODEL	kVA max	kVA cont	kVA max	kVA cont	Starting	Brand		Cylinder	cm3	Hp (max) 3600	Cons. 75%(h/l)	Standard panel										
		50 Hz	60 Hz		Engine Technical Data												Tank l	L	W	H	Kg	LWA (*)
SINGLE-PHASE																						
H3000	2,8	2,5	3,1	2,8	M	Honda	GX160	1	163	5,5	0,9	QM114	--	3,6	59	39	38	36	96			
H3500	3.4	3.1	4	3.5	M	Honda	GX200	1	196	6.5	1	QM114	--	3.6	59	39	38	40	96			
H5000	4.5	4.1	5.4	5	M	Honda	GX270	1	270	9	1.5	QM115	--	6	78	52	56	62	95			
H5000E	4.5	4.1	5.4	5	E	Honda	GX270	1	270	9	1.5	QM115	ACP 0411	6	78	52	56	69	95			
H8000	7.2	6.5	8	7.2	M	Honda	GX390	1	389	13	1.9	QM116	--	6.5	78	52	56	73	96			
H8000E	7.2	6.5	8	7.2	E	Honda	GX390	1	389	13	1.9	QM116	ACP 0411	6.5	78	52	56	80	96			
THREE-PHASE																						

H6500T	5.4	4.9	6.5	5.6	M	Honda	GX270	1	270	9	1.5	QM301	--	6	78	52	56	72	95
H6500TE	5.4	4.9	6.5	5.6	E	Honda	GX270	1	270	9	1.5	QM301	ACP 0411	6	78	52	56	79	95
H8000T	7.5	6.8	8.3	7.5	M	Honda	GX390	1	389	13	1.9	QM301	--	6.5	78	52	56	78	96
H8000TE	7.5	6.8	8.3	7.5	E	Honda	GX390	1	389	13	1.9	QM301	ACP 0411	6.5	78	52	56	85	96

Edit Table

Legend: (*) = Tested value; noise level compliant with European regulation 2000/14/CE * Noise level not compliant with European regulation 2000/14/CE

> CONTROL PANEL

QM 114



QM 115



QM 116



QM 301



ACP 0411 ATS



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com