



PRINT THIS PAGE

1500 rpm 50 Hz – cos ϕ 0,8 400/230V 1800 rpm 60 Hz – cos ϕ 0,8 voltage on request

ENERMAXSERIES Cummins



STANDARD EQUIPMENT

- Lifting eye
- Fully bunded fuel tank
- Integrated fuel tank
- Exhaust gas silencer
- Air filter
- Manual control panel with circuit breaker
- Distribution panel with output sockets standard up to 30 A
- 12/24V battery
- Soundproof canopy
- Forklift pockets

DIESEL Water Cooled

> ALTERNATORS



ENERMAX-CUMMINS

MODEL	kVA LTP	kVA PRP	kVA LTP	kVA PRP		Regulator	Cylinder	cm3	kWm 1500 rpm	kWm 1800 rpm	(l/h) 1500 rpm	(l/h) 1800 rpm	Aspiration	Standard panel	Automatic panel	dB(A) (•) 7 m					
50 Hz		60 Hz		Engine						Cons. 70%		Cons. 70%				Tank l		L	W	H	Kg
THREE-PHASE																					
CU91TSX**	88	80	99	88	QSB5G3	E	4	4500	74	83	14,1	16	T	AUS7310	ACP 7320	68	185	258	113	164	1350

CU100TSX**	100	90	110	100	QSB5G4	E	4	4500	82	93	15,1	18	T	AUS7310	ACP 7320	68	185	258	113	164	1450
CU111TSX**	110	100	125	113	QSB5G5	E	4	4500	90	101	17,1	20,1	T	AUS7310	ACP 7320	68	185	258	113	164	1650
CU151TSX**	150	135	156	141	QSB5G6	E	4	4500	121	125	22,9	25,2	T	AUS7310	ACP 7320	68	185	297	113	175	1820
CU201TSX**	200	180	220	200	QSB7G4	E	6	6690	154	170	29,8	33,2	T	AUS7310	ACP 7320	68	270	338	113	185	2460
CU221TSX**	220	200	250	225	QSB7G5	E	6	6690	168	194	32,2	35,5	T	AUS7310	ACP 7320	68	270	338	113	185	2300
CU275TSX**	275	250	317	288	QSL9G3	E	6	8800	217	248	44,4	51,5	T	AUS7310	ACP 7320	68	600	390	120	223	3380
CU330TSX	330	300	378	344	QSL9G5	E	6	8900	258	293	41,5	49,1	T	AUS7310	ACP 7320	68	600	390	120	223	3600
CU331TSX**	330	300	385	350	QSL9G7	E	6	8800	260	300	50,3	59,7	T	AUS7310	ACP 7320	68	600	390	120	223	3680
CU450TSX*	450	410	487	445	QSX15G4	E	6	15000	348	383	60,6	65,7	T	AUS7310	ACP 7320	69	1000	425	200	223	5700
CU501TSX**	500	455	495	450	QSX15G6	E	6	15000	396	383	66	66,4	T	AUS7310	ACP 7320	69	1000	485	200	230	5770
CU600TSX*	550	500	490	450	QSX15G8	E	6	15000	426	383	71,1	66,4	T	AUS7310	ACP 7320	69	1000	485	200	230	5900
CU650TSX	--	--	618	562	QSX15G9	E	6	15000	--	476	--	80,5	T	AUS7310	ACP 7320	69	1000	485	200	230	5970
CU715TSX*	715	650	688	625	QSK19G4	E	6	19000	555	526	101,1	95,3	T	AUS7310	ACP 7320	69	1300	555	220	230	7900
CU750TSX*	--	--	748	680	QSK19G5	E	6	19000	--	574	--	102,1	T	AUS7310	ACP 7320	69	1300	555	220	230	7950
CU901TSX	880	800	1000	910	QSK23G3	E	6	23100	682	776	111	125,7	T	AUS7310	ACP 7320	75	1300	555	220	230	9400

Edit Table

Legend: N= natural T= turbo (*) = Noise level compliant with European regulation 2000/14/CE

> CONTROL PANEL



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com