

PRINT THIS PAGE

1500 rpm 50 Hz – cos ϕ 0,8 400/230V 1800 rpm 60 Hz – cos ϕ 0,8 voltage on request

ENERMAX SERIES KOHLER.



STANDARD EQUIPMENT

- Lifting eye
- Fully bunded fuel tank
- Integrated fuel tank
- Exhaust gas silencer
- Air filter
- Manual control panel with circuit breaker
- Distribution panel with output sockets standard up to 30 A
- 12V battery
- Soundproof canopy
- Forklift pockets

DIESEL Water Cooled

> ALTERNATORS



ENERMAX-KOHLER

MODEL	kVA LTP	kVA PRP	kVA LTP	kVA PRP		Regulator	Cylinder	cm ³	kWm 1500 rpm	kWm 1800 rpm	(l/h) 1500 rpm	(l/h) 1800 rpm	Aspiration	Standard panel	Automatic panel	dB(A) (+) 7 m					
	50 Hz		60 Hz		Engine						Cons. 70%	Cons. 70%					Tank l	L	W	H	Kg

SINGLE-PHASE																					
KL6MSX	5.3	4.5	6.5	6	KDW702	M	2	686	5	5.9	1.1	1.3	N	AUS7310-13	ACP 7320	65	75	150	80	125	450
KL8MSX	8.6	7.6	9.5	9	KDW1003	M	3	1028	7.7	9.1	1.8	2.1	N	AUS7310-13	ACP 7320	65	75	150	80	125	480
KL11MSX	12	11	14.3	13	KDW1404	M	4	1372	10.5	12.3	2.5	2.9	N	AUS7310-17	ACP 7320	65	75	150	80	125	500
KL16MSX	16.2	14.7	19.8	18	KDW1603	M	3	1649	14	16.8	3.3	3.9	N	AUS7310-17	ACP 7320	65	75	150	80	125	550
KL22MSX	21	19	25.2	22.9	KDW2204	M	4	2199	17.7	20.5	3.9	4.4	N	AUS7310-17	ACP 7320	65	75	150	80	125	590
THREE-PHASE																					
KL6TSX	5.7	5.1	6.7	6.1	KDW702	M	2	686	5	5.9	1.1	1.3	N	AUS7310-14	ACP 7320	65	75	150	80	125	450
KL8TSX	8.8	8	10.5	9.6	KDW1003	M	3	1028	7.7	9.1	1.8	2.1	N	AUS7310-14	ACP 7320	65	75	150	80	125	480
KL11TSX	12	11	14.2	13.2	KDW1404	M	4	1372	10.5	12.3	2.5	2.9	N	AUS7310-14	ACP 7320	65	75	150	80	125	500
KL16TSX	16.5	15	19.8	18	KDW1603	M	3	1649	14.1	16.8	3.3	3.9	N	AUS7310-15	ACP 7320	65	75	150	80	125	550
KL22TSX	21	19	25.2	22.9	KDW2204	M	4	2199	17.7	20.5	3.9	4.4	N	AUS7310-15	ACP 7320	65	75	150	80	125	590
KL33TSX	33	30	--	--	KDI2504TM	M	4	2482	37.3	--	5.4	--	T	AUS7310	ACP 7320	67	135	196	98	136	1020
KL45TSX	45	41	---	---	KDI2504TM	M	4	2482	37.3	---	6.6	---	T	AUS7310	ACP 7320	67	135	196	98	136	1050
KL71TSX	69	63	78	71	KDI3404TM	M	4	3400	55.5	63	10.8	12.8	T	AUS7310	ACP 7320	67	185	230	113	158	1220
STAGE III A																					
THREE-PHASE																					
KL23TSX**	21	19	22	20	KDI1903M	M	3	1861	17.3	18.6	3.2	3.3	N	AUS7310-15	ACP 7320	65	75	150	80	133	610
KL28TSX**	27.5	25	30.8	28	KDI2504M	M	4	2482	23.1	26.4	4.2	4.6	N	AUS7310	ACP 7320	65	75	196	98	136	660
KL35TSX**	33	30	40	36	KDI2504TM	M	4	2482	33.1	33.1	5.4	5.9	T	AUS7310	ACP 7320	67	135	196	98	136	970
KL38TSX**	38.5	35	40.7	37	KDI2504TM	M	4	2482	33.1	33.1	5.7	6	T	AUS7310	ACP 7320	67	135	196	98	136	1000
KL73TSX**	69	63	78	71	KDI3404TM	M	4	3400	55.5	63	10.8	12.8	T	AUS7310	ACP 7320	67	185	230	113	158	1220

Edit Table

Legend: N= natural T= turbo (*) = Noise level compliant with European regulation 2000/14/CE

> CONTROL PANEL

