

[PRINT THIS PAGE](#)

1500 rpm 50 Hz – cos ϕ 0,8 400/230V **1800 rpm** 60 Hz – cos ϕ 0,8 voltage on request

ENERMAX SERIES



STANDARD EQUIPMENT

- Lifting eye
- Fully bunded fuel tank
- Integrated fuel tank
- Exhaust gas silencer
- Air filter
- Manual control panel with circuit breaker
- Distribution panel with output sockets standard up to 30 A
- 12V battery
- Soundproof canopy
- Forklift pockets

DIESEL Water Cooled

> ALTERNATORS






ENERMAX-VOLVO

MODEL	kVA LTP	kVA PRP	kVA LTP	kVA PRP		Regulator	Cylinder	cm3	kWm 1500 rpm	kWm 1800 rpm	(l/h) 1500 rpm	(l/h) 1800 rpm	Aspiration	Standard panel	Automatic panel	dB(A) (•) 7 m					
	50 Hz		60 Hz		Engine						Cons. 70%	Cons. 70%					Tank l	L	W	H	Kg

SINGLE-PHASE																					
MI8MSX*	7	6.3	8.8	8	L3E SD	M	3	952	6.2	7.8	1.5	1.8	N	AUS7310-13	ACP 7320	65	75	150	80	125	510
MI12MSX*	11	10	13.2	12	S3L2 SD	M	3	1318	9.7	11.8	2.1	2.5	N	AUS7310-17	ACP 7320	65	75	150	80	125	560
MI17MSX*	14.8	13.5	18.8	17	S4L2 SD	M	4	1758	13.7	16.2	2.8	3.4	N	AUS7310-17	ACP 7320	65	75	150	80	125	560
MI23MSX*	21	19	25.3	23	S4Q2 SD	M	4	2505	19.5	22.8	4	4.8	N	AUS7310-17	ACP 7320	65	75	160	80	133	570
THREE-PHASE																					
MI8TSX*	7.5	6.5	8.8	8	L3E SD	M	3	952	6.2	7.8	1.5	1.8	N	AUS7310-14	ACP 7320	65	75	150	80	125	510
MI12TSX*	11.5	10.5	14.2	12.9	S3L2 SD	M	3	1318	9.7	11.8	2	2.5	N	AUS7310-14	ACP 7320	65	75	150	80	125	560
MI17TSX*	16.5	15	19.8	18	S4L2 SD	M	4	1758	13.7	16.2	2.9	3.5	N	AUS7310-15	ACP 7320	65	75	150	80	125	560
MI23TSX*	22	20	28	25.8	S4Q2 SD	M	4	2505	19.5	22.8	4	5	N	AUS7310-15	ACP 7320	65	75	160	80	133	570
MI35TSX*	33	30	39	36	S4S SD	M	4	3331	27.5	33.4	5.9	6.9	N	AUS7310	ACP 7320	67	135	196	98	136	960
MI45TSX*	42	40	54	49	S4S DT SD	M	4	3331	36.7	43.7	7.1	8.6	T	AUS7310	ACP 7320	67	135	196	98	136	1000
MI65TSX	65	60	--	--	4EG-TA61SDK	M	4	3331	52.8	--	9.1	--	T	AUS7310	ACP 7320	67	185	230	113	158	1320
STAGE III A																					
THREE-PHASE																					
MI22TSX**	22	20	--	--	S4Q2Z361SD	M	4	2505	19.6	--	4	--	N	AUS7310-15	ACP 7320	65	75	160	80	133	570
MI36TSX**	33	30	--	--	S4S2361SD	M	4	3331	27.6	--	5.8	--	N	AUS7310	ACP 7320	67	135	196	98	136	960
MI41TSX**	44	40	--	--	S4SDT23DT61SD	M	4	3331	35.3	--	7.2	--	T	AUS7310	ACP 7320	67	135	196	98	136	1000

Edit Table

Legend: N= natural T= turbo (*) = Noise level compliant with European regulation 2000/14/CE

> CONTROL PANEL



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com