

[HOME](#)[ABOUT US](#)[PRODUCTS](#)[HYBRID](#)[FOCUS ARCHIVE](#)[NEWS ARCHIVE](#)[DOWNLOAD](#)[CONTACT](#)[English](#)

[Home](#) / [LIGHTING TOWERS](#) / [FT SERIES](#) / [SX](#)

[PRINT THIS PAGE](#)

3000 rpm 50 Hz – cos ϕ 0,8 230V – 400/230V 3600 rpm 60 Hz – cos ϕ 0,8 voltage on request

SX



POWERED by
KOHLER

STANDARD EQUIPMENT

- SX Series generating set
 - Pneumatic mast in anodized aluminium (max height 5,5 mt)
 - 4x500W halogen spotlights
 - Trolley with pneumatic wheels for manual displacement
 - 4 stabilising feet separately adjustable
 - Connection cable
- spotlights/generating set

DIESEL Air Cooled

SX LIGHTING TOWER

MODEL	kVA max	kVA cont	kVA max	kVA cont	Starting	Brand		Cylinder	cm3	Hp (max) 3600	Cons. 75%/4/1	LWA				H MAX CM	LUMEN TOT	Standard panel		
	50 Hz		60 Hz					Engine Technical Data						L	W	H	Kg			
DIESEL GENERATORS																				
SINGLE-PHASE																				
LD5000ESX-FT	4.6	4.2	5.1	4.6	E	Kohler	15LD350	1	349	7.5	1.2	95	20	104	82	180	191	550	35000	QM105
LD7500ESX-FT	6.4	5.8	7.5	6.8	E	Kohler	15LD440	1	442	11	1.6	95	20	104	82	180	211	550	35000	QM106
THREE-PHASE																				
LD5000TESX-FT	4.6	4.2	5.1	4.6	E	Kohler	15LD350	1	349	7.5	1.2	95	20	104	82	180	201	550	35000	QM305
LD7500TESX-FT	6.4	5.8	7.5	6.8	E	Kohler	15LD440	1	442	11	1.6	95	20	104	82	180	221	550	35000	QM306

Legend: (+) = Tested value; noise level compliant with European regulation 2000/14/CE

> CONTROL PANEL



TECNOGEN S.p.A.
Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy
PIVA/CF 01126350537

ITALY SALES DEPARTMENT
Tel: +39 0523 512401
Fax: +39 0523 504453
E mail: italy@tecnogen.com

EXPORT DEPARTMENT
Tel: +39 0523 512440 Fax: +39 0523 504453
E mail: export@tecnogen.com