

PRINT THIS PAGE

1500 rpm 50 Hz - cos φ 0,8 400/230V 1800 rpm 60 Hz - cos φ 0,8 voltage on request

# FUSTEQ KOHLER



## STANDARD EQUIPMENT

- Lifting eye
- Fully bunded fuel tank
- Integrated fuel tank
- Cooling system with electric fans controlled by Inverter
- Air filter
- Manual control panel with circuit breaker
- Distribution panel with output sockets standard up to 30 A
- 12V battery
- Ultra-silent canopy
- Forklift guides

DIESEL Water Cooled

> ALTERNATORS



## FUSTEQ-KOHLER

MODEL	kVA LTP	kVA PRP	kVA LTP	kVA PRP	Engine	Regulator	Cylinder	cm3	kWm 1500 rpm	kWm 1800 rpm	(l/h) 1500 rpm	Fuel saving (l)	(l/h) 1800 rpm	Fuel saving (l)	Aspiration	Standard panel	Synchronising control panel	dB(A) (+) 7 m	Tank l	L	W	H	Kg
	50 Hz		60 Hz						Mechanical radiator	Electric radiator	Mechanical radiator	Electric radiator	Cons. 70%	In 1000 h operation	Cons. 70%	In 1000 h operation	(option)						





**TECNOGEN S.p.A.**

Strada per Ponte Riglio, 25  
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

**ITALY SALES DEPARTMENT**

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: [italy@tecnogen.com](mailto:italy@tecnogen.com)

**EXPORT DEPARTMENT**

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: [export@tecnogen.com](mailto:export@tecnogen.com)