

PRINT THIS PAGE

HL LED LIGHTING TOWER

1500 rpm – 50 Hz – $\cos \phi$ 0,8 – 220V – 240V

| 1800 rpm – 60 Hz – $\cos \phi$ 0,8

| 1800 rpm – 48V



>MOBILE BOX



STANDARD EQUIPMENT

- Hydraulic mast made of galvanized steel
- Maximum height **9 m**
- Rotation 350°
- Fast and automatic deployment with safety system
- 140 litres fuel tank
- Noise level 60 dB(A)
- Liquids bunding
- 4 deploying stabilizers

>ENGINE

KOHLER. **YANMAR**

MODEL	NUMBER OF HEADS	W PER LAMP	TOTAL W	CURRENT	VOLTAGE V	50 Hz		60 Hz		Engine	cm3	kWm	kWm	fuel consumption (l/h)		Aspiration	TANK (l)	DIMENSIONS (cm)			MAXIMUM SIZE (cm)			WEIGHT	STANDARD PANEL
						kVA LTP	kVA PRP	kVA LTP	kVA PRP			1500 rpm	1800 rpm	1500 rpm*	1800 rpm*			L	W	H	L	W	H		
																									
MB MOBILE BOX LED																									
48V DC - WITH TRAILER																									
MB 9504 KL	4	250 W	1000 W	DC	48 V	-	-	-	-	KOHLER LDW 702	686	-	5,9	-	0,35	N	110	235	148	225	235	202	883	1060	AUS 401-80
MB 9504 KL	4	300 W	1200 W	DC	48 V	-	-	-	-	KOHLER LDW 702	686	-	5,9	-	0,46	N	110	235	148	225	235	202	883	1065	AUS 401-80
MB 9404 YM	4	250 W	1000 W	DC	48 V	-	-	-	-	YANMAR 2TNV70	570	-	5,8	-	0,34	N	110	235	148	225	235	202	883	1050	AUS 401-80
MB 9404 YM	4	300 W	1200 W	DC	48 V	-	-	-	-	YANMAR 2TNV70	570	-	5,8	-	0,34	N	110	235	148	225	235	202	883	1055	AUS 401-80

*Consumption is calculated with all the lights turned on at the same time

> CONTROL PANEL



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com

