

PRINT THIS PAGE

HL LED LIGHTING TOWER

1500 rpm – 50 Hz – $\cos \phi$ 0,8 – 220V – 240V | 1800 rpm – 60 Hz – $\cos \phi$ 0,8 | 1800 rpm – 48V

> MINING TOWER LED



STANDARD EQUIPMENT

- Hydraulic mast made of galvanized steel
- Maximum height **9 m**
- Rotation 350°
- Fast and automatic deployment with safety system
- 140 litres fuel tank
- Noise level 60 dB(A)
- Liquids bunding
- 4 deploying stabilizers



>ENGINE



MODEL	NUMBER OF HEADS	W PER LAMP	TOTAL W	CURRENT	VOLTAGE V	50 Hz		60 Hz		Engine	cm3	kWm	kWm	fuel consumption (l/h)		Aspiration	TANK (l)	DIMENSIONS (cm)			MAXIMUM SIZE (cm)			WEIGHT	STANDARD PANEL
						kVA LTP	kVA PRP	kVA LTP	kVA PRP					1500 rpm	1800 rpm			1500 rpm*	1800 rpm*	L	W	H	L		
MT MINING TOWER LED																									
SINGLE -PHASE																									
MT 9810 PK**	8+2	330+250 W	3140 W	AC	230 V	8,8	8	12	11	PERKINS 403D-11G	1131	8,4	10,3	1,3	1,3	N	250	244	190	225	419	237	920	2000	MCP 120-80
MT 9810 KL**	8+2	330+250 W	3140 W	AC	230 V	8,6	7,6	9,5	9	KOHLER KDW 1003	1028	7,6	9,1	1,4	1,3	N	250	244	190	225	419	237	920	2000	MCP 120-80

*Consumption is calculated with all the lights turned on at the same time

> CONTROL PANEL



MCP120-80



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com