

PRINT THIS PAGE

HL LED LIGHTING TOWER

1500 rpm – 50 Hz – $\cos \phi$ 0,8 – 220V – 240V | 1800 rpm – 60 Hz – $\cos \phi$ 0,8 | 1800 rpm – 48V



>SITE LIGHT



>SOFT LIGHT



STANDARD EQUIPMENT

- Hydraulic mast made of galvanized steel
- Maximum height **9 m**
- Rotation 350°
- Fast and automatic deployment with safety system
- 140 litres fuel tank
- Noise level 60 dB(A)
- Liquids bunding
- 4 deploying stabilizers

>ENGINE

 **Perkins**

KOHLER

YANMAR

MODEL	NUMBER OF HEADS	W PER LAMP	TOTAL W	CURRENT	VOLTAGE V	50 Hz		60 Hz		Engine	cm3	kWm	kWm	fuel consumption (l/h)	fuel consumption (l/h)	Aspiration	TANK (l)	DIMENSIONS (cm)			MAXIMUM SIZE (cm)			WEIGHT	STANDARD PANEL
						KVA LTP	KVA PRP	KVA LTP	KVA PRP									1500 rpm	1800 rpm	L	W	H	L		
														1500 rpm*	1800 rpm*										
SL SITE LIGHT LED																									
SINGLE-PHASE																									
SL 9508 KL	8	250 W	2000 W	AC	230 V	5.3	4.5	6.5	6	KOHLER KDW 702	686	5	5.9	0.8	0.7	N	140	245	130	230	245	280	920	1100	MCP 120-80
SL 9606 YM	6	250 W	1500 W	AC	230 V	5	4.5	6.6	6	YANMAR 2TNV70	570	4.2	5.8	0.6	0.6	N	140	245	130	230	245	280	920	1050	MCP 120-80
SL 9608 YM	8	250 W	2000 W	AC	230 V	5	4.5	6.6	6	YANMAR 2TNV70	570	4.2	5.8	0.6	0.6	N	140	245	130	230	245	280	920	1100	MCP 120-80
SL 9808 PK**	8	250 W	2000W	AC	230 V	8.8	8	12	11	PERKINS 403D-11G	1131	8.4	10.3	0.8	0.8	N	140	245	130	230	245	280	920	1120	MCP 120-80
SL 9810 PK**	10	250 W	2500 W	AC	230 V	8.8	8	12	11	PERKINS 403D-11G	1131	8.4	10.3	1	1	N	140	245	130	230	245	280	920	1150	MCP 120-80
SL 9810 PK**	8 + 2	330+250 W	3140 W	AC	230 V	8.8	8	12	11	PERKINS 403D-11G	1131	8.4	10.3	1.3	1.3	N	140	245	130	230	245	280	920	1180	MCP 120-80
SO SOFT LIGHT LED																									
SINGLE-PHASE																									
SB 9508 KL	8	250 W	2000 W	AC	230 V	5.3	4.5	6.5	6	KOHLER KDW 702	686	5	5.9	0.8	0.7	N	140	245	130	230	245	280	920	1120	MCP 120-80
SB 9608 YM	8	250 W	2000 W	AC	230 V	5	4.5	6.6	6	YANMAR 2TNV70	570	4.2	5.8	0.6	0.6	N	140	245	130	230	245	280	920	1180	MCP 120-80

*Consumption is calculated with all the lights turned on at the same time

> CONTROL PANEL



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

PIVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401
Fax: +39 0523 504453
E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453
E mail: export@tecnogen.com

