

PRINT THIS PAGE 

1500 rpm 50 Hz – cos ϕ 0,8 230V-400/230V 1800 rpm 60 Hz – cos ϕ 0,8 voltage on request

ENERMAX SERIES  



STANDARD EQUIPMENT

- Lifting eye
- Fully bunded fuel tank
- Integrated fuel tank
- Exhaust gas silencer
- Air filter
- Manual control panel with circuit breaker
- Distribution panel with output sockets standard up to 30 A
- 12/24V battery
- Soundproof canopy
- Forklift pockets

DIESEL Water Cooled

> ALTERNATORS

LEROY-SOMER
Nidec

STAMFORD

 **meccalte**

 **MarelliMotori**
Power generation

MODEL	KVA LTP	KVA PRP	KVA LTP	KVA PRP		Regulator	Cylinder	cm3	kWm 1500 rpm	kWm 1800 rpm	(l/h) 1500 rpm	(l/h) 1800 rpm	Aspiration	Standard panel	Automatic control panel	dB(A) (+) 7 m						
	50 Hz		60 Hz		Engine				Mechanical radiator	Mechanical radiator	Cons. 70%	Cons. 70%			(option)		Tank I	AdBlue tank I	L	W	H	Kg
IV226TSX V	220	200	---	---	N67	E	6	6728	176	---	30.4	---	T	AUS7310	ACP7320	67	600	78	390	113	239	3470
IV276TSX V	275	250	---	---	CURSOR9	E	6	8700	215.7	---	37.7	---	T	AUS7310	ACP7320	67	1000	81	425	200	223	3960
IV336TSX V	330	300	---	---	CURSOR9	E	6	8700	257.8	---	46.1	---	T	AUS7310	ACP7320	67	1000	81	425	200	223	4350
IV356TSX V	385	350	---	---	CURSOR13	E	6	12882	299	---	53.7	---	T	AUS7310	ACP7320	68	1000	178	425	200	223	5300
IV446TSX V	440	400	---	---	CURSOR13	E	6	12882	340	---	62.4	---	T	AUS7310	ACP7320	68	1000	178	425	200	223	5750

Legend: N= natural T= turbo

> CONTROL PANEL



TECNOGEN S.p.A.
Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy
PIVA/CF 01126350337

ITALY SALES DEPARTMENT
Tel: +39 0523 512401
Fax: +39 0523 504453
E mail: italy@tecnogen.com

EXPORT DEPARTMENT
Tel: +39 0523 512440 Fax: +39 0523 504453
E mail: export@tecnogen.com