

PRINT THIS PAGE

1500 rpm 50 Hz – cos ϕ 0,8 230V-400/230V 1800 rpm 60 Hz – cos ϕ 0,8 voltage on request

ENERMAX SERIES VOLVO PENTA



> ALTERNATORS

LEROY-SOMER
Nidec

STAMFORD

meccalte

MarelliMotori
Power generation

STANDARD EQUIPMENT



- Lifting eye (for canopy models only)
- Fully bunded fuel tank
- Integrated fuel tank
- Exhaust gas silencer
- Air filter
- Manual control panel with circuit breaker
- Distribution panel with output sockets standard up to 30 A
- Battery
- Soundproof canopy/container
- Forklift pockets

DIESEL Water Cooled

MODEL	KVA LTP	KVA PRP	KVA LTP	KVA PRP		Regulator	Cylinder	cm3	kWm 1500 rpm	kWm 1800 rpm	(l/h) 1500 rpm	(l/h) 1800 rpm	Aspiration	Standard panel	Automatic control panel	dB(A) (+) 7 m						
	50 Hz		60 Hz		Engine				Mechanical radiator	Mechanical radiator	Cons. 70%	Cons. 70%			(option)		Tank l	AdBlue tank l	L	W	H	Kg
VO725TSX V	726	660	770	700	TWD1683GE	E	6	16120	570	596	88,0	100,0	T	AUS7310	ACP7320	68	1833	160	485	200	230	7780
VO1450 V-40 V	1452	1320	1540	1400	TWD1683GE x 2	E	6	16120	1140	1192	176,0	200,0	T	SCP8610	ATS+ DSE 705	68	3600	320	40' HC container			24240

Legend: N= natural T= turbo

> CONTROL PANEL



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com