



HOME

ABOUT US

PRODUCTS

HYBRID

FOCUS ARCHIVE

NEWS ARCHIVE

DOWNLOAD

CONTACT

English



Home / 3000/3600 rpm / SX SERIES – DIESEL AIR COOLED

PRINT THIS PAGE

3000 rpm 50 Hz – cos ϕ 0,8 230V – 400/230V 3600 rpm 60 Hz – cos ϕ 0,8 **voltage on request**

SX SERIES

DIESEL Air Cooled

KOHLER



STANDARD EQUIPMENT

- Hot galvanized steel soundproof canopy
- Lifting eye
- Exhaust gas silencer
- Air filter
- Fuel tank 20 lt
- Key start switch
- Distribution panel with output sockets with circuit breaker, 0,03 A ELCB optional
- 12V Battery on electric started models


SX SERIES

MODEL	kVA max	kVA cont	kVA max	kVA cont	Starting	Brand		Cylinder	cm3	Hp (max) 3600	Cons. 75%(h/l)	Standard panel							
	50 Hz		60 Hz														Engine Technical Data		
SINGLE-PHASE																			
LD5000ESX	4.6	4.2	5.1	4.7	E	Kohler	15LD350	1	349	7.5	1.2	QM106	ACP 0411	20	75	56	62	140	95
LD7500ESX	6.4	5.8	7.5	6.8	E	Kohler	15LD440	1	442	11	1.5	QM106	ACP 0411	20	75	56	62	160	95
THREE-PHASE																			
LD5000TESX	4.6	4.2	5.1	4.7	E	Kohler	15LD350	1	349	7.5	1.2	QM306	ACP 0411	20	75	56	62	150	95
LD7500TESX	6.4	5.8	7.5	6.8	E	Kohler	15LD440	1	442	11	1.6	QM306	ACP 0411	20	75	56	62	170	95


Edit Table

> CONTROL PANEL


QM 106



QM 306



ACP 0411 ATS



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com