

[PRINT THIS PAGE](#) 

1800 rpm 60 Hz – cos ϕ 0,8 208 V 3 Ph – 480V 3 Ph – 240/120V 1Ph

ENERMAX SERIES



STANDARD EQUIPMENT

- Lifting eye
- Fully bunded fuel tank
- Integrated fuel tank
- Exhaust gas silencer
- Air filter
- Manual control panel with circuit breaker
- Battery
- Soundproof canopy
- Forklift pockets

DIESEL Water Cooled

> ALTERNATORS

LEROY-SOMER
Nidec

STAMFORD

**meccalte**

 **MarelliMotori**
Power generation

MODEL	KVA LTP	KVA PRP	KVA LTP	KVA PRP		Regulator	Cylinder	cm3	kWm 1800 rpm		Aspiration	Standard panel	Automatic control panel	dB(A) (+) 7 m			 inch (cm)			
					Engine				Mechanical radiator	Cons. 70% U.S. gal/h (l/h)					Diesel tank U.S. gal (l)	DEF tank U.S. gal (l)	L	W	H	Lb (kg)
FP130TSX 4	140	127.5	112	102	N45	E	4	4485	110	5,4 (20,6)	T	AUS7310	ACP7320	66	49 (185)	11 (43)	117 (297)	44 (113)	69 (175)	7055 (3200)
FP145TSX 4	158	144	126.5	115	N67	E	6	6700	123	6 (23)	T	AUS7310	ACP7320	67	159 (600)	20 (78)	154 (390)	44 (113)	88 (223)	7165 (3250)
FP170TSX 4	182.5	165	146	132	N67	E	6	6700	143	7 (26,5)	T	AUS7310	ACP7320	67	159 (600)	20 (78)	154 (390)	44 (113)	88 (223)	7275 (3300)
FP200TSX 4	215	195	172	156	N67	E	6	6700	168	7,9 (30)	T	AUS7310	ACP7320	67	159 (600)	20 (78)	154 (390)	44 (113)	88 (223)	7430 (3370)
FP225TSX 4	250	225	200	180	N67	E	6	6700	194	9,1 (34,6)	T	AUS7310	ACP7320	67	159 (600)	20 (78)	154 (390)	44 (113)	88 (223)	7540 (3420)
FP250TSX 4	275	250	220	200	CURSOR9	E	6	8700	216	10 (38)	T	AUS7310	ACP7320	67	264 (1000)	21 (81)	167 (425)	79 (200)	88 (223)	11795 (5350)
FP275TSX 4	306	275	245	220	CURSOR9	E	6	8700	236	11,2 (42,3)	T	AUS7310	ACP7320	67	264 (1000)	21 (81)	167 (425)	79 (200)	88 (223)	12015 (5450)
FP300TSX 4	337.5	304	270	243	CURSOR9	E	6	8700	260	12,4 (46,9)	T	AUS7310	ACP7320	67	264 (1000)	21 (81)	167 (425)	79 (200)	88 (223)	12125 (5500)
FP330TSX 4	363	328	290	262	CURSOR9	E	6	8700	279	13,3 (50,3)	T	AUS7310	ACP7320	68	264 (1000)	21 (81)	167 (425)	79 (200)	88 (223)	12346 (5600)
FP340TSX 4	375	341.3	300	273	CURSOR13	E	6	12882	290	13,9 (52,6)	T	AUS7310	ACP7320	68	264 (1000)	47 (178)	167 (425)	79 (200)	88 (223)	13228 (6000)
FP370TSX 4	407.5	370	326	296	CURSOR13	E	6	12882	315	15 (56,8)	T	AUS7310	ACP7320	68	264 (1000)	47 (178)	167 (425)	79 (200)	88 (223)	13669 (6200)
FP420TSX 4	462.5	417.5	370	334	CURSOR13	E	6	12882	355	17,3 (65,4)	T	AUS7310	ACP7320	68	264 (1000)	47 (178)	191 (485)	79 (200)	91 (230)	14462 (6560)

Legend: N= *natural* T= *turbo*

> CONTROL PANEL



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com

