

PRINT THIS PAGE 

1800 rpm 60 Hz – cos  $\phi$  0,8 208 V 3 Ph – 480V 3 Ph – 240/120V 1Ph

## ENERMAX SERIES KOHLER.



### STANDARD EQUIPMENT

- Lifting eye
- Fully bunded fuel tank
- Integrated fuel tank
- Exhaust gas silencer
- Air filter
- Manual control panel with circuit breaker
- Battery
- Soundproof canopy
- Forklift pockets

DIESEL Water Cooled






> ALTERNATORS

LEROY-SOMER  
Nidec

STAMFORD


meccalte

MarelliMotori  
Power generation

MODEL	KVA LTP	KVA PRP	KVA LTP	KVA PRP	 Engine	Regulator	Cylinder	cm3	kWm 1800 rpm		Aspiration	Standard panel	Automatic control panel	dB(A) (+) 7 m	 Diesel tank U.S gal (l)	 DEF tank U.S gal (l)	 inch (cm)			 Lb (kg)
									Mechanical radiator	Cons. 70% U.S. gal/h (l/h)							L	W	H	
KL5TSX 4	6.6	6	5.5	5	KDW702	M	2	686	5.7	0,4 (1,7)	N	AUS7310	ACP7320	65	20 (75)	NA	59 (150)	31 (80)	49 (125)	992 (450)
KL9TSX 4	10.5	9.5	8.4	7.5	KDW1003	M	3	1028	8.9	0,6 (2,2)	N	AUS7310	ACP7320	65	20 (75)	NA	59 (150)	31 (80)	49 (125)	1058 (480)
KL13TSX 4	14.5	13.2	12	11	KDW1404	M	4	1372	12.1	0,7 (2,7)	N	AUS7310	ACP7320	65	20 (75)	NA	59 (150)	31 (80)	49 (125)	1102 (500)
KL25TSX 4	23	21	18	17	KDI1903M	M	3	1861	18.6	1 (3,8)	N	AUS7310	ACP7320	65	20 (75)	NA	59 (150)	31 (80)	49 (125)	1345 (610)
KL35TSX 4	40	37.5	33	30	KDI1903TCR	E	3	1861	32.5	1,9 (7,2)	T	AUS7310	ACP7320	67	49 (185)	NA	91 (230)	44 (113)	62 (158)	2315 (1050)
KL50TSX 4	53.7	48.7	43	39	KDI2504TCR	E	4	2482	41.6	2,2 (8,4)	T	AUS7310	ACP7320	67	49 (185)	NA	91 (230)	44 (113)	62 (158)	2425 (1100)
KL80TSX 4	89	81	71.5	65	KDI3404TCR SCR	E	4	3400	76	3,6 (13,6)	T	AUS7310	ACP7320	67	49 (185)	4 (16)	100 (255)	44 (113)	65 (164)	3307 (1500)

Legend: N= natural T= turbo

### > CONTROL PANEL



**TECNOGEN S.p.A.**

Strada per Ponte Riglio, 25  
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

**ITALY SALES DEPARTMENT**

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: [italy@tecnogen.com](mailto:italy@tecnogen.com)

**EXPORT DEPARTMENT**

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: [export@tecnogen.com](mailto:export@tecnogen.com)