

[HOME](#)[ABOUT US](#)[PRODUCTS](#)[HYBRID](#)[FOCUS ARCHIVE](#)[NEWS ARCHIVE](#)[DOWNLOAD](#)[CONTACT](#)[English](#)[PRINT THIS PAGE](#) [Home](#) / [TIER 4 FINAL](#) / [Megasilent series](#) / [MEGASILENT VOLVO PENTA](#)

1800 rpm 60 Hz – cos ϕ 0,8 208 V 3 Ph – 480V 3 Ph

MEGASILENT VOLVO PENTA



STANDARD EQUIPMENT

- Lifting eye
- Fully bunded fuel tank
- Integrated fuel tank
- Cooling system with electric fans controlled by Inverter
- Air filter
- Manual control panel with circuit breaker
- Battery
- Ultra-silent canopy
- Forklift guides

DIESEL Water Cooled

> ALTERNATORS

LEROY-SOMER
Nidec

STAMFORD

meccalte

 **Marelli Motori**
Power generation

MODEL	KVA LTP	KVA PRP	KVA LTP	KVA PRP		Regulator	Cylinder	cm3	kWm 1800 rpm			Fuel saving	Aspiration	Standard panel	Synchronising control panel	dB(A) (+) 7 m			 inch (cm)			
	60 Hz				Engine				Mechanical radiator	Electric radiator	Cons. 70% U.S. gal/h (l/h)	in 1000 hours operation			(option)		Diesel tank U.S. gal (l)	DEF tank U.S. gal (l)	L	W	H	Lb (kg)
VO660FQ 4	720	656	576	525	TWD1672GE	E	6	16120	532	555	25,9 (98)	---	T	AUS7310	SCP8610	63	476 (1800)	42 (160)	197 (500)	83 (210)	94 (240)	20503 (9300)
VO725FQ 4	788	715	630	572	TWD1673GE	E	6	16120	595	618	28 (106)	---	T	AUS7310	SCP8610	63	476 (1800)	42 (160)	197 (500)	83 (210)	94 (240)	20944 (9500)
VO1250FQ-30 4*	1438	1312	1150	1050	TWD1672GE x 2	E	6	16120	532	1110	51,8 (196)	---	T	AUS7310	SCP8610	63	1128 (4270)	84 (320)	30' HC Fusteq container			41997 (19000)

*Available also in 40'HC Fusteq container
Legend: N= *natural* T= *turbo*

> CONTROL PANEL



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com

