

PRINT THIS PAGE

XO LED SERIES

Lighting Tower HYDRAULIC DEPLOYMENT



HYDRAULIC DEPLOYMENT

4 x 250W or 300W
adjustable LED spotlights,
48V DC



STANDARD EQUIPMENT

- 4 x 250 W or 300 W LED spotlights
- Hydraulic deployment to full height of 7m
- STAINLESS STEEL MAST
- Mast in vertical position during transport, 350°rotation
- 140 litres fuel tank
- Noise level 63 dB(A) @ 7 meters
- 3 deploying stabilizers
- Fork pockets
- Road trailer
- Easy and quick to service and maintain

DIESEL Water Cooled

>ENGINE

YANMAR

MODEL	NUMBER	W PER LAMP	TOTAL W	CURRENT	DC GENERATOR	Output power	Governor	r.p.m.	Engine	cm3	fuel consumption	Aspiration	TANK (l)	DIMENSIONS (cm)			MAXIMUM SIZE (cm)			WEIGHT	STANDARD
	OF HEADS			VOLTAGE V		kWm					(l/h)			L	W	H	L	W	H		PANEL
XOH 7004 YM	4	250 W	1000 W	48V DC	NSM	5.8	M	1800	YANMAR 2TNV70	570	0.34	N	140	253	143	245	253	256	740	855	AUS 401-80
XOH 7004 YM	4	300 W	1200 W	48V DC	NSM	5.8	M	1800	YANMAR 2TNV70	570	0.41	N	140	253	143	245	253	256	740	860	AUS 401-80

Legend: Name** engine emissions compliant Eu stage III A

> CONTROL PANEL

AUS 401-80



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com

